



HEATERKING





HEATERKING

Heaterking is one of SAWO's top-of-the-line sauna heater designed by world renowned Finnish designer **Stefan Lindfors**.



The heaterking is a very unique and creative sauna heater. The heaterking, with exemplary looks is also with well defined characters.

This heater is with thick, high premium stainless metal sheet casing that is laser cut with an intricate junglefire pattern. It is a floor standing heater that can handle up to 360kg of stones. A stone spacer is included. It kept proper airflow inside the heater that fasten the sauna room heat-up time.

The heaterking is operated with a separate control or it can be ordered as an *Ni model.

Heaterking heaters are available from 3kW up to 24kW rating capacity.

**Ni Models are with built-in power controller inside the heater. Connect an Innova user interface to operate.*



WALL



ROUND



CORNER



Two parts metal casing

Putting the stones below the heater becomes very handy when the casing for tall heaters are in two parts. It is recommended to place the larger stones at the bottom. Use only bigger than 35mm sized stones so that there is a good airflow in the heater.

Place the top casing and continue adding stones little over the rim after completing the stone placement at the lower part of the heater.



Stone Spacer

The stone spacer separates the stones from the heating elements. It makes the heating elements to last longer as they are not in contact with the stones.

The stone spacer also improves the air ventilation inside the heater. A proper airflow inside the heater makes the heater to heat up fast.



Adjustable Leg Support

When the flooring is not even, just twist the height of the adjustable leg support to get the correct balance of the heater.



INNOVA
POWER CONTROLLER



FIRECONTROL

Heater Controls

The Heaterking can be operated using a Separate Control (NS) or Ni Controls (Ni).

NS Heaters are using external control. SAWO has several list of separate controls that is fully equipped with multi sauna functions. One good recommendation for the Heaterking is the Firecontrol. It is a touch screen LCD control with Innova based operations where user can set a weekly sauna session, adjust the light brightness, fan, function for heater and steamer (combi), ready for household automation, power interruption saving settings, and many more...


Ni heaters are with Innova Power Controller hardware placed inside the heater. Innova Touch Stainless Steel, Innova Touch, Classic or Classic 2.0 user interface can be used.



STAINLESS STEEL TOUCH



CLASSIC 2.0



Ni HEATER

Extra Accessories

Heater Guards and Collars

As the heater can reach up to 120 deg. Celcius, a **Heater Guard** is needed to prevent accidental contact with the heater. Heater guards are compatible with Heaterking Round models only. Available in Cedar or Aspen wood.

The excessive heat near the wood can create burn marks. **Collars** does not only protect the wood but also add elegance in the sauna room. Collars can vary as soapstone, stainless steel or a Cedar wood.



HEATER GUARD



COLLAR



Code: HP01-070

Water Volume: 0,7 Liters

Size: 109 x 109 x 267mm


Cozy Tank

Cozy Tank is a mechanical humidifier that increases the moisture inside the sauna.


Place the Cozy Tank between the heating elements and stones around it. The water inside the cozy tank will evaporate to create a soft mild steam. The addition of humid air neutralizes the dry sauna heat.

Additional aroma oil can be diluted together with water for a rejuvenating sauna smell.


Safety Distances & Technical Data



HEATER MODEL	A	B	SAUNA ROOM (m³)			SIZE OF HEATER (mm)			STONES (kg)		CONTROL
			kW	MIN	MAX	WIDTH	DEPTH	HEIGHT	WITH SPACER	NO SPACER	
DRFT2-30NS	150	1900	3.0	2	4	250	250	1325	60	70	separate
DRFT3-35NS	100	1900	3.5	3	6	250	250	1325	60	70	separate
DRFT3-45NS	100	1900	4.5	3	6	250	250	1325	60	70	separate
DRFT3-60NS	150	1900	6.0	5	8	250	250	1325	60	70	separate
DRFT4-60NS	100	1900	6.0	5	9	295	295	1325	90	105	separate
DRFT4-80NS	200	1900	8.0	7	13	295	295	1325	90	105	separate
DRFT5-90NS	200	1900	9.0	8	14	295	295	1325	90	105	separate
DRFT6-80NS / DRFT6-80Ni	100	1900	8.0	7	14	355	355	1325	100	160	separate / Innova
DRFT6-90NS / DRFT6-90Ni	100	1900	9.0	8	15	355	355	1325	100	160	separate / Innova
DRFT6-105NS / DRFT6-105Ni	150	1900	10.5	9	16	355	355	1325	100	160	separate / Innova
DRFT6-120NS / DRFT6-120Ni	200	2100	12.0	11	18	355	355	1325	100	160	separate / Innova
DRFT9-105NS / DRFT9-105Ni	150	2100	10.5	10	16	425	425	1325	165	230	separate / Innova
DRFT9-120NS / DRFT9-120Ni	150	2100	12.0	11	20	425	425	1325	165	230	separate / Innova
DRFT9-150NS / DRFT9-150Ni	200	2100	15.0	14	25	425	425	1325	165	230	separate / Innova
DRFT9-180NS	200	2100	18.0	18	28	425	425	1325	165	230	separate
DRFT12-150NS / DRFT12-150Ni	200	2300	15.0	15	26	525	525	1325	220	360	separate / Innova
DRFT12-180NS / DRFT12-180Ni	200	2300	18.0	18	30	525	525	1325	220	360	separate / Innova
DRFT12-210NS / DRFT12-210Ni	200	2300	21.0	22	35	525	525	1325	220	360	separate / Innova
DRFT12-240NS / DRFT12-240Ni	200	2300	24.0	24	40	525	525	1325	220	360	separate / Innova



HEATER MODEL	A	B	SAUNA ROOM (m³)			SIZE OF HEATER (mm)			STONES (kg)		CONTROL
			kW	MIN	MAX	WIDTH	DEPTH	HEIGHT	WITH SPACER	NO SPACER	
DRFT3-35NS-WL	100	1900	3.5	3	6	395	220	1440	60	80	separate
DRFT3-45NS-WL	100	1900	4.5	3	6	395	220	1440	60	80	separate
DRFT3-60NS-WL	100	1900	6.0	5	8	395	220	1440	60	80	separate
DRFT6-80NS-WL	100	1900	8.0	7	14	550	300	1475	105	160	separate
DRFT6-90NS-WL	100	1900	9.0	8	15	550	300	1475	105	160	separate
DRFT6-105NS-WL	100	1900	10.5	9	16	550	300	1475	105	160	separate
DRFT6-120NS-WL	100	2100	12.0	11	18	550	300	1475	105	160	separate
DRFT9-105NS-WL	100	2100	10.5	10	16	650	350	1510	115	180	separate
DRFT9-120NS-WL	100	2100	12.0	11	20	650	350	1510	115	180	separate
DRFT9-150NS-WL	100	2100	15.0	14	25	650	350	1510	115	180	separate
DRFT9-180NS-WL	100	2100	18.0	18	28	650	350	1510	115	180	separate
DRFT12-150NS-WL	100	2300	15.0	15	26	790	420	1545	165	250	separate
DRFT12-180NS-WL	100	2300	18.0	18	30	790	420	1545	165	250	separate
DRFT12-210NS-WL	100	2300	21.0	22	35	790	420	1545	165	250	separate
DRFT12-240NS-WL	100	2300	24.0	24	40	790	420	1545	165	250	separate



HEATER MODEL	A	B	SAUNA ROOM (m³)			SIZE OF HEATER (mm)			STONES (kg)		CONTROL
			kW	MIN	MAX	WIDTH	DEPTH	HEIGHT	WITH SPACER	NO SPACER	
DRFT3-35NS-CNR	100	1900	3.5	3	6	300	300	1410	45	70	separate
DRFT3-45NS-CNR	100	1900	4.5	3	6	300	300	1410	45	70	separate
DRFT3-60NS-CNR	100	1900	6.0	5	8	300	300	1410	45	70	separate
DRFT6-80NS-CNR	100	1900	8.0	7	14	410	410	1430	80	160	separate
DRFT6-90NS-CNR	100	1900	9.0	8	15	410	410	1430	80	160	separate
DRFT6-105NS-CNR	100	1900	10.5	9	16	410	410	1430	80	160	separate
DRFT6-120NS-CNR	100	2100	12.0	11	18	410	410	1430	80	160	separate



**SAWO
DRAGONFIRE**

Manufactured by:



www.sawo.com
info@sawo.com